



AQURON® 007™

Proven Since 1985

Concrete Cleaner HIGH PERFORMANCE CLEANERS

MANUFACTURER

AQURON® Corporation International
Post Office Box 758
Rockwall, Texas 75087 U.S.A
972-722-5444 Phone
972-722-6412 Fax
800-342-4649 Toll Free
888-412-1543 Toll Free Fax
E-Mail: info@aquron.com
Website: www.aquron.com

PRODUCT DESCRIPTION

AQURON® 007™ Concrete Cleaner is a clear to amber environmentally friendly, non-toxic, odorless liquid.

BASIC USE

AQURON® 007™ Concrete Cleaner is an environmentally neutral and user friendly, water borne cleaner formulated for concrete. **AQURON® 007™ Concrete Cleaner** is formulated to clean unsightly oil and grease contaminants from concrete and work to restore its original coloration.

Once **AQURON® 007™ Concrete Cleaner** contacts concrete it begins to liquefy oil and grease at and below the surface. As **AQURON® 007™ Concrete Cleaner** rises to the surface, let dry. Rinse with high-pressure wash to remove dried product. Repeat process until stains no longer remain.

PRECAUTIONS

AQURON® 007™ Concrete Cleaner is always applied to water dampened concrete. Area to be cleaned must be water damp when applying **AQURON® 007™ Concrete Cleaner**

AQURON® 007™ Concrete Cleaner can cause redness of skin tissue if repeated contact is made. Goggles and gloves should be worn during application of **AQURON® 007™ Concrete Cleaner**.

COMPOSITION

AQURON® 007™ Concrete Cleaner is an odorless, clear to slightly amber liquid acidic cleaner.

PHYSICAL PROPERTIES

Physical	liquid
Color	clear/slightly amber
Odor	none
Flash Point	none
Specific Gravity	1.1 to 1.2
pH	±1
Toxicity	none
Boiling Point	216°F/108°C
Freeze Temperature	32°F/0°C
Freeze Harm	none
Weight per US Gallon	8.70lbs/4.08kg
Environmentally	friendly
User	friendly
Shelf life	indefinite
Flammability	none
VOC/VOS Content	none
Pollutants	none
Waste Disposal Method	non-hazardous
Paintable	yes

INSTALLATION SUGGESTIONS

Job Conditions

1. Do not proceed with use of **AQURON® 007™ Concrete Cleaner** when ambient temperature and/or substrate temperatures are less than 45°F/9°C. (Works faster in warm weather.)
2. If surface is wet from rain, broom out the standing water leaving a damp surface for application of **AQURON® 007™ Concrete Cleaner**.
3. Protect all adjacent surfaces to prevent contact with painted surfaces as contact can soften paint.

Application Procedures

1. **AQURON® 007™ Concrete Cleaner** should be applied using pump tank garden type sprayer.

Application Procedures Cont...

2. Pre-dampen concrete to be cleaned with water then apply AQURON® 007™ Concrete Cleaner to dark oily grease areas first.
3. Apply AQURON® 007™ Concrete Cleaner to dampened dark areas with pump tank compression sprayer.
4. Once AQURON® 007™ Concrete Cleaner has been applied to damp concrete agitate surface of dark areas with stiff-bristle brush.
5. Once area to be cleaned has received AQURON® 007™ Concrete Cleaner and has dried, wash treated area to remove white powder that has resulted from treatment. (All treated areas must dry completely before washing with high-pressure washer takes place.)
6. Repeat steps 1 through 5 until all dark areas have been removed.
7. Diluting AQURON® 007™ Concrete Cleaner from 10:1 clean entire area of concrete to be treated, to even the overall color. (a test area is recommended to determine dilution rate.)
8. Clean pump sprayer and all equipment with water before storing equipment.
9. Use safety equipment as necessary.

CLEAN-UP AND SAFETY

- Caution should be taken as area of cleaning can be slippery until completely cured.
- Goggles, gloves, and rubber boots should be worn during cleaning process.
- Clean all equipment using water before storing.

SHELF LIFE

Shelf life is indefinite provided containers are kept tightly sealed when not in use.

PACKAGING

AQURON® 007™ Concrete Cleaner is available in 5 gallon/19.9 liters and 55 gallon/213.4 liters.

AQURON® 007™ Concrete Cleaner is also available in bulk containers.

TECHNICAL SERVICES

Technical information and assistance may be obtained from your local dealer, or by calling the technical department of the AQURON Corporation at (972) 722-5444, (800) 342-4649 Office, or (972) 722-6412 FAX or toll free FAX (888) 412-1543. E-mail welcome – info@aquron.com

Warranties and Limitations of Liability

Aquron Corporation ("Seller") warrants that if any goods supplied prove defective in workmanship or materials, that Seller shall replace them or refund their purchase price. Aquron Corporation offers a performance warranty for this Aquron® product. The warranty for the performance of this Aquron® product must be requested from the Aquron Corporation and initiated prior to applying this Aquron® product. Failure to initiate warranty of performance prior to application, holds harmless Aquron Corporation of any liability arising from its use, and user assumes all risk and liabilities whatsoever in connection therewith. The terms of this paragraph may not be orally modified. There are no warranties express or implied which extend beyond the face herewith.

Local Area Representative